


Opis produktu

# 62764-866-WL-500

## 62764-866-WL-500 WD 180 flex multi sens. WL



### Ogólne informacje

Typ produktu	62764-866-WL-500
Kod zamówieniowy	2CKA006200A0249
Numer EAN	4011395292723
Opis katalogowy	62764-866-WL-500 WD 180 flex multi sens. WL

Opis

Movement detector sensor with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times. For detection down to the floor. For detection in stairwells. With 4 detection levels. In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With time-controlled basic illumination function. With time-controlled night anti-glare function. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Remote operation via the Bluetooth and smartphone/tablet app. Multi-lens: suitable also for mounting heights of 2.20 m. Extension of the detection range by means of master/slave combination. Timer with Astro function. Automatic switchover from summer time to winter time (switch-off function). With continuous light/continuous Off function. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 54 sectors with 224 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U.

### Installation

Instrukcje i podręczniki	2CKA000073B5189
Typ montażu	Flush Mounted

## Dane techniczne

Arkusz danych, informacja techniczna	No document needed
Kompatybilne systemy magistralowe	free@home wireless
Grupa produktowa	flexTronics free@home
Minimalny czas przełączania	Switch-On 30 second [unit of time]
Skład chemiczny baterii	Lithium
Typ Baterii	Button Cell
Waga baterii	0.07 g
Liczba baterii	1

## Design

Material	Thermoplastic
Kolor	stainless steel

## Material Compliance

Dane RoHS	2CKA200000E7438
Status RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Deklaracja REACH	2CKA309999E9999
REACH Information	False - does not contains substances > 0.1 mass percentage
Szablon raportowania CMRT	9AKK108468A3363

## Normy środowiskowe

Temperatura powietrza otoczenia	-5...45 °C
Stopień ochrony	IP20

## Wymiary

Szerokość netto	63 mm
Wysokość netto	63 mm
Głębokość / długość netto	44 mm
Masa netto	34 g

## Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności UE No declaration needed

## Klasyfikacje

ETIM 9 EC000138 - Sensor element for movement sensor  
 eClass V11.0 : 27144008  
 Kategoria WEEE 5. Small Equipment (No External Dimension More Than 50 cm)  
 WEEE B2C / B2B Business To Consumer

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A3042	Relay insert 1 gang(s) 230 V	64811 U-500	1	sztuka
2CKA006800A3048	Standard Outputs 1 gang(s) 230 V	64814 U-500	1	sztuka
2CKA006800A3045	Relay insert 2 gang(s) 230 V	64821 U-500	1	sztuka
2CKA006500A0013	Dimmer insert Push button 1 gang(s) 230 V	64851 U-500	1	sztuka
2CKA006800A3051	Bus Coupling Units / Push Button Coupling Units 1 gang(s) 230 V	64891 U-500	1	sztuka

## Kategorie

Produkty niskiego napięcia i systemy → Building and Home Automation Solutions → free@home → User Operation → Solo → Motion Detectors

