

CEILINE III 20W downlight



Power **20 W**

Luminous flux* **1600 lm (90°)**

Colour of light **Neutral white**

Degree of protection (IP) **IP20**

Voltage **230 V**

Colour temperature **4000 K**

Beam angle **90 °**



 Declaration of Conformity





 Photometric file



 3D model

Technical data:

Code	SLI022008NW
Power	20 W
Nominal current	90 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	1600 lm (90°)
Luminous flux**	1600 lm (360°)
Lamp efficacy	80 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	190x90 mm
Mounting hole	170 mm
Weight	0.5 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



*applies to the LED source used, **Luminaire luminous flux
A version with CNBOP-PIB* certificate is also available (valid only in Poland).