

CEILINE III 10W downlight



Power	10 W	Voltage	230 V
Luminous flux*	850 lm (90°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	90 °
Degree of protection (IP)	IP44/IP20		




 Photometric file

SLI022006CW_IP44

Technical data:

Code	SLI022006CW_IP44
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Useful luminous flux*	850 lm (90°)
Luminous flux**	850 lm (360°)
Lamp efficacy	85 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	TWORZYWO SZTUCZNE
Degree of protection (IP)	IP44/IP20
Colour	White
Dimension (AxBxC)	150x80 mm
Mounting hole	130 mm
For use	Inside/Outside
Assembly method	Recessed
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux
A version with CNBOP-PIB* certificate is also available (valid only in Poland).