


## NOCTIS LUX 2 10W floodlight with motion sensor




CE

Power	<b>10 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>850 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>100 °</b>
Degree of protection (IP)	<b>IP44</b>		




See more on dedicated page 





 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI029041CW_CZUJNIK
Power	10 W
Nominal current	70 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	850 lm (120°)
Luminous flux**	830/850 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	160x104x25 mm
Weight	0.26 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux

Motion sensor PIR (sensor regulated, range: 2-10 m., operating time: 10 s. - 7 m., ambient light: 3 - 2000 LUX)