


## ALGINE 32W led panel




Power	<b>32 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3300 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>120 °</b>
UGR	<b>&lt;22</b>	IK	<b>06</b>



 User manual



 Declaration of Conformity



 Photometric file



Technical data:

Code	SLI035012CW
Power	32 W
Nominal current	154 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	32 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3300 lm (120°)
Luminous flux**	3300 lm (360°)
Lamp efficacy	103 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
UGR	<22
RA	80
Uniformity of color SDCM max	5
Dimmable	OPTION
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x10 mm
Mounting hole	575x575 mm
Weight	2.09 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux  
Also available as DALI, DIM, DIMRF.