

ANDROMEDA COB LED 25W NW 3F BLACK (3 PHASES) 36DEG 60DEG



Power	25 W	Voltage	230 V
Luminous flux*	3250 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	36, 60 °
Degree of protection (IP)	IP20		




 [User manual](#)



 [Declaration of Conformity](#)

Technical data:

Code	SLI033018NW_PW
Power	25 W
Nominal current	120 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	LIFUD
Power factor	0.9
Useful luminous flux*	3250 lm (360°)
Luminous flux**	2650 lm (360°)
Lamp efficacy	130 lm/W
Luminous intensity	6100 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	36, 60 °
RA	80
Light source included	+
Producer of LED diodes	SANAN
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	170 x 160 x 74 mm
Weight	1.041 kg
For use	Inside
Assembly method	On 3-circuit system
Application	INT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux