

## ALGINE 32W led panel



---

|                 |                       |                           |               |
|-----------------|-----------------------|---------------------------|---------------|
| Power           | <b>32 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>3300 lm (120°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b>  | Beam angle                | <b>120 °</b>  |
| IK              | <b>06</b>             | Degree of protection (IP) | <b>IP20</b>   |

---



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

|                              |                                   |
|------------------------------|-----------------------------------|
| Code                         | SLI035014NW                       |
| Power                        | 32 W                              |
| Nominal current              | 154 mA                            |
| Voltage                      | 230 V                             |
| Energy efficiency class      | E                                 |
| Energy consumption           | 32 kWh/1000h                      |
| Frequency                    | 50HZ Hz                           |
| Protection class             | II                                |
| Power factor                 | 0.9                               |
| Useful luminous flux*        | 3300 lm (120°)                    |
| Luminous flux**              | 3240 lm (360°)                    |
| Lamp efficacy                | 103 lm/W                          |
| Colour temperature           | 4000 K                            |
| Colour of light              | Neutral white                     |
| Beam angle                   | 120 °                             |
| RA                           | 80                                |
| Uniformity of color SDCM max | 5                                 |
| Working temperature range    | -20/+40 °                         |
| Lifespan                     | 17000 h                           |
| Housing material             | Aluminum, PLASTIC                 |
| IK                           | 06                                |
| Degree of protection (IP)    | IP20                              |
| Colour                       | White                             |
| Dimension (AxBxC)            | 295x1195x10 mm                    |
| Mounting hole                | 275x1175 mm                       |
| Weight                       | 2.25 kg                           |
| For use                      | Inside                            |
| Assembly method              | Recessed/On the ceiling/Suspended |
| Application                  | INT                               |
| Made in                      | PRC                               |



\*applies to the LED source used, \*\*Luminaire luminous flux

Also available as SMART, DALI, DIM and version with CNBOP-PIB\* certificate (valid only in Poland).