

## ALGINE 32W led panel



Power	<b>32 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3200 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>



 Declaration of Conformity



 Photometric file



 3D model

**Technical data:**

Code	SLI035039NW
Power	32 W
Nominal current	140 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	32 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	3200 lm (120°)
Luminous flux**	3200 lm (360°)
Lamp efficacy	100 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x10 mm
Mounting hole	575x575 mm
Weight	2.2 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC
Other	L80B50 50000h MTBF 80000h



\*applies to the LED source used. \*\*Luminaire luminous flux  
Also available as DALI, DIM, DIMRF.