


## ALGINE 45W led panel




Power	<b>45 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4820 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>



 User manual



 Declaration of Conformity



 Photometric file



**Technical data:**

Code	SLI035037WW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	4820 lm (360°)
Luminous flux**	4400 lm (360°)
Lamp efficacy	97 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x10 mm
Mounting hole	575x575 mm
Weight	2.09 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC
Other	L80B50 50000h MTBF 80000h



\*applies to the LED source used. \*\*Luminaire luminous flux  
Also available as DALI, DIM, DIMRF.