

ECLAIR 18W 24V façade lamp



Power **18 W**

Luminous flux* **1000 lm (90°)**

Colour of light **WW**

Degree of protection (IP) **IP65**

Voltage **24 V**

Colour temperature **3000 K**

Beam angle **45 °**



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI001011WW
Power	18 W
Nominal current	750 mA
Voltage	24 V
Energy efficiency class	G
Energy consumption	20 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1000 lm (90°)
Luminous flux**	1000 lm (360°)
Lamp efficacy	55 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	45 °
Light source included	+
Uniformity of color SDCM max	6
Dimmable	+
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	500x43x85 mm
Weight	1.2 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux
*Light colour 4000 K available on request. Requires 24V power supply.