# **Product Environmental Profile**

#### MULTIFIX ABOX 1M 12-27 mm, 6 RIG STUB+BF








#### **General information**

Representative product	MULTIFIX ABOX 1M 12-27 mm, 6 RIG STUB+BF - IMT80274				
Description of the product	The main purpose of Multifix Abox is to make installation work easier, to house modern devices with a larger depth.				
Functional unit	Protect persons during 20 years against direct contact with live parts and allow grouping monitoring, control and protection devices in a single enclosure having the following dimensions 149.5 x 133.2 x 57.4, while protecting against the penetration of solid objects and liquids (IP30) in accordance with the standard IEC 60529.				

### Constituent materials



## **Substance assessment**

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate – BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website <a href="http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page">http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</a>


## Additional environmental information

The MULTIFIX ABOX 1M 12-27 mm, 6 RIG STUB+BF presents the following relevent environmental aspects						
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified					
	Weight and volume of the packaging optimized, based on the European Union's packaging directive					
Distribution	Packaging weight is 20.8 g, consisting of cardboard (99.63%), paper (0.37%)					
	Product distribution optimised by setting up local distribution centres					
Installation	The product does not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials is accounted during the installation phase (including transport to disposal).					
Use	The product does not require special maintenance operations.					
	End of life optimized to decrease the am	ount of waste and allow recovery of the product components and materials				
End of life	No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.					
	Recyclability potential: 60%	Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).				

# **Environmental impacts**

Reference life time	20 years				
Product category	Unequipped enclosures and cabinets				
Installation elements	No special components needed				
Use scenario	Non applicable for unequipped enclosures and cabinets				
Geographical representativeness	Sweden, Norway, Finland				
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production.				
	Manufacturing	Installation	Use	End of life	
Energy model used	Manufacturing plant: Polplast, Poland	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	

Compulsory indicators	MULTIFIX ABOX 1M 12-27 mm, 6 RIG STUB+BF - IMT80274						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	4.28E-06	4.28E-06	8.47E-10	0*	0*	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	1.71E-03	1.56E-03	9.66E-05	4.70E-06	0*	4.12E-05
Contribution to water eutrophication	kg PO <sub>4</sub> 3- eq	9.92E-04	9.57E-04	2.23E-05	1.14E-06	0*	1.14E-05
Contribution to global warming	kg CO <sub>2</sub> eq	8.15E-01	7.72E-01	2.12E-02	1.13E-03	0*	2.16E-02
Contribution to ozone layer depletion	kg CFC11 eq	2.80E-08	2.71E-08	4.29E-11	0*	0*	9.10E-10
Contribution to photochemical oxidation	kg C₂H₄ eq	1.78E-04	1.67E-04	6.89E-06	3.51E-07	0*	4.31E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	2.42E-03	2.40E-03	1.89E-06	0*	0*	1.87E-05
Total Primary Energy	MJ	1.56E+01	1.51E+01	2.99E-01	1.47E-02	0*	2.01E-01



Optional indicators		MULTIFIX ABOX 1M 12-27 mm, 6 RIG STUB+BF - IMT80274				4	
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	6.70E+00	6.22E+00	2.97E-01	1.46E-02	0*	1.61E-01
Contribution to air pollution	m³	5.01E+01	4.77E+01	9.00E-01	4.49E-02	0*	1.45E+00
Contribution to water pollution	m³	2.71E+02	2.65E+02	3.48E+00	1.71E-01	0*	1.74E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	1.43E-02	1.43E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	5.90E-01	5.89E-01	3.99E-04	0*	0*	2.23E-04
Total use of non-renewable primary energy resources	MJ	1.50E+01	1.45E+01	2.99E-01	1.47E-02	0*	2.01E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.76E-01	1.75E-01	3.99E-04	2.29E-05	0*	2.23E-04
Use of renewable primary energy resources used as raw material	MJ	4.14E-01	4.14E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.11E+01	1.06E+01	2.99E-01	1.47E-02	0*	2.01E-01
Use of non renewable primary energy resources used as raw material	MJ	3.96E+00	3.96E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	4.09E-01	2.16E-01	0*	0*	0*	1.93E-01
Non hazardous waste disposed	kg	2.98E-01	2.97E-01	7.52E-04	1.53E-04	0*	6.16E-04
Radioactive waste disposed	kg	2.20E-04	2.18E-04	5.35E-07	3.01E-08	0*	9.66E-07
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.19E-01	1.57E-02	0*	2.07E-02	0*	8.21E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	2.88E-03	0*	0*	0*	0*	2.88E-03
Exported Energy	MJ	6.58E-05	6.19E-06	0*	5.96E-05	0*	0*

<sup>\*</sup> represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP2002008_V2	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	09/2020	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org

Independent verification of the declaration and data

Internal X External

The elements of the present PEP cannot be compared with elements from another program.

Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »

Schneider Electric Industries SAS

Country Customer Care Center http://www.schneider-electric.com/contact

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP2002008\_V2 © 2019 - Schneider Electric – All rights reserved

09/2020