


H4371*



H4372*

1. USE

Audible and optical signalling devices: pilot lamps.


2. RANGE

PILOT LAMPS WITH INTEGRATED LED

	No. of diffusers	Colours of diffusers	Power supply	Current voltage	Power
H4371B/12	1	blue	127 Vav	26 mA	300 mW
H4371B/24	1	blue	24 Vac	27 mA	700 mW
H4371B/230	1	blue	127 and 230 Vac	21 mA	500 mW
H4371T/12	1	transparent	127 Vav	26 mA	300 mW
H4371T/24	1	transparent	24 Vac	27 mA	700 mW
H4371T/230	1	transparent	127 and 230 Vac	21 mA	500 mW
H4371R/12	1	red	127 Vav	26 mA	300 mW
H4371R/24	1	red	24 Vac	27 mA	700 mW
H4371R/230	1	red	127 and 230 Vac	21 mA	500 mW
H4371V/12	1	green	127 Vav	26 mA	300 mW
H4371V/24	1	green	24 Vac	27 mA	700 mW
H4371V/230	1	green	127 and 230 Vac	21 mA	500 mW

	No. of diffusers	Colours of diffusers	Power supply	Current voltage	Power
H4372RT/12	2	red + transp.	127 Vav	26 mA	300 mW
H4372RT/24	2	red + transp.	24 Vac	27 mA	700 mW
H4372RT/230	2	red + transp.	127 and 230 Vac	21 mA	500 mW
H4372RV/12	2	red + green	127 Vav	26 mA	300 mW
H4372RV/24	2	red + green	24 Vac	27 mA	700 mW
H4372RV/230	2	red + green	127 and 230 Vac	21 mA	500 mW

3. OVERALL DIMENSIONS (mm)



References	A	B	C	D
H4371*	45	22.5	31	9.5
H4372*	45	22.5	31	9.5

4. CONNECTION

Stripping length (rigid or flexible cables): 11 mm for screwless terminals
9 mm for screw terminals

Depending of the items numbers.

5. TECHNICAL CHARACTERISTICS

■ **5.1 Protection index**

Penetration by solid bodies/liquid: IP 21 D
Impact test: IK 04

■ **5.2 Material characteristics**

Material: Polycarbonate for mechanism case
PC for key cover

Halogen free.

UV resistant.

Self-extinguishing:

- + 850° C / 30 s for insulating parts holding live parts in place.
- + 650° C / 30 s for other parts made of insulating materials.

■ **5.3 Climatic characteristics**

Storage and operating temperatures: - 5° C to + 35° C

6. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Caution: A preliminary test should be carried out if other specific cleaning products are to be used.

7. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing.
Refer to e. catalogue.