

# Product Environmental Profile

**UNDER-DESK MULTI-OUTLETS to be connected -  
2P+E French and German standards sockets**



## LEGRAND'S ENVIRONMENTAL COMMITMENTS

• **Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

• **Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

• **Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



## REFERENCE PRODUCT

<b>Function</b>	Distribute the electrical network to the workstation via 6 sockets 2P+E F/B standard for 20 years.
<b>Reference Product</b>	
	Cat.No 0 734 02
	UNDER-DESK MULTI-OUTLETS 6x2P+E F/B empty.

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



## PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers
• 0 734 00
• 0 734 01
• 0 734 02
• 0 734 03
• 0 734 04
• 0 734 05
• 0 734 06
• 0 734 19
• 0 734 20
• 0 734 21
• 0 734 22

# Product Environmental Profile

**UNDER-DESK MULTI-OUTLETS to be connected -  
2P+E French and German standards sockets**



## ■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

<b>Total weight of Reference Product</b>	<b>1007 g</b> (all packaging included)				
Plastics as % of weight		Metals as % of weight		Other as % of weight	
PC-ABS	11.3 %	Aluminium	67.3 %	Cables / Electric wires	1.3 %
ABS	3.8 %	Copper alloys	6.8 %		
PA	0.2 %	Steel	1.8 %		
Other plastic	< 0.1 %				
PET	< 0.1 %				
PP	< 0.1 %				
<b>Packaging as % of weight</b>					
PP	0.6 %			Paper	3.7 %
				Wood	3.2 %
<b>Total plastics</b>	<b>15.9 %</b>	<b>Total metals</b>	<b>75.9 %</b>	<b>Total others</b>	<b>8.2 %</b>

Estimated recycled material content: 39 % by mass.



## ■ MANUFACTURE

This Reference Product comes from sites that, in their majority, have received ISO14001 certification.



## ■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 780 km by road from our warehouse to the local point of distribution into the market in Europe.

Packaging is compliant with european directive 2004/12/EU concerning packaging and packaging waste. At their end of life, its recyclability rate is 90 % (in % of packaging weight).



## ■ INSTALLATION

For the installation of the product, only standard tools are needed.



## ■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

# Product Environmental Profile

**UNDER-DESK MULTI-OUTLETS to be connected -  
2P+E French and German standards sockets**



## END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. This product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• **Extended producer responsibility:**

The sale of this product is subject to a contribution to eco-organisations in each country responsible for managing end of life products in the field of application of the European Waste Electronic and Electrical Equipment Directive.

• **Recyclability rate:**

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 98 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 15 %
- metal materials (excluding packaging) : 76 %
- packaging (all types of materials) : 7 %



## ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end of life. It is representative from products marketed and used in Europe, in compliance with the local current standards.

For each phase, the following modelling elements were taken in account:

<b>Manufacture</b>	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
<b>Distribution</b>	Transport between the last Group distribution centre and an average delivery point in the sales area.
<b>Installation</b>	The end of life of the packaging.
<b>Use</b>	<ul style="list-style-type: none"> <li>• Product category: PSR-0003-ed1.1-2015 10 16, 3.2.3.2. Pre-equipped service poles, service posts and multi-outlet extensions.</li> <li>• Use scenario: non-continuous operation for 20 years at 30% of rated load during 30% of the time. This modelling duration does not constitute a minimum durability requirement.</li> <li>• Energy model: Electricity Mix; Europe 27 - 2008.</li> </ul>
<b>End of life</b>	The default end of life scenario maximizing the impacts.
<b>Software and database used</b>	EIME & database CODDE-2018-11

# Product Environmental Profile

**UNDER-DESK MULTI-OUTLETS to be connected -  
2P+E French and German standards sockets**



## SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
<b>Global warming</b>	1.88E+01	kgCO <sub>2</sub> eq.	1.06E+01	56 %	3.91E-02	< 1 %	4.72E-03	< 1 %	8.07E+00	43 %	6.91E-02	< 1 %
<b>Ozone depletion</b>	2.40E-06	kgCFC-11 eq.	1.87E-06	78 %	7.92E-11	< 1 %	3.89E-11	< 1 %	5.26E-07	22 %	8.27E-10	< 1 %
<b>Acidification of soils and water</b>	8.24E-02	kgSO <sub>2</sub> eq.	4.83E-02	59 %	1.76E-04	< 1 %	2.16E-05	< 1 %	3.37E-02	41 %	2.84E-04	< 1 %
<b>Water eutrophication</b>	1.93E-02	kg(PO <sub>4</sub> ) <sup>3-</sup> eq.	1.67E-02	87 %	4.04E-05	< 1 %	1.74E-05	< 1 %	2.03E-03	11 %	4.34E-04	2 %
<b>Photochemical ozone formation</b>	4.54E-03	kgC <sub>2</sub> H <sub>4</sub> eq.	2.66E-03	58 %	1.25E-05	< 1 %	1.55E-06	< 1 %	1.85E-03	41 %	2.15E-05	< 1 %
<b>Depletion of abiotic resources - elements</b>	2.90E-03	kgSb eq.	2.90E-03	100 %	1.56E-09	< 1 %	2.16E-10	< 1 %	7.01E-07	< 1 %	3.35E-09	< 1 %
<b>Total use of primary energy</b>	2.89E+02	MJ	1.27E+02	44 %	5.53E-01	< 1 %	6.34E-02	< 1 %	1.61E+02	56 %	8.33E-01	< 1 %
<b>Net use of fresh water</b>	2.95E+01	m <sup>3</sup>	2.60E-01	< 1 %	3.50E-06	< 1 %	1.55E-06	< 1 %	2.93E+01	99 %	3.02E-05	< 1 %
<b>Depletion of abiotic resources - fossil fuels</b>	1.68E+02	MJ	7.53E+01	45 %	5.49E-01	< 1 %	6.14E-02	< 1 %	9.16E+01	54 %	7.95E-01	< 1 %
<b>Water pollution</b>	2.20E+03	m <sup>3</sup>	1.85E+03	84 %	6.43E+00	< 1 %	7.14E-01	< 1 %	3.33E+02	15 %	9.27E+00	< 1 %
<b>Air pollution</b>	1.42E+03	m <sup>3</sup>	1.07E+03	75 %	1.60E+00	< 1 %	4.53E-01	< 1 %	3.47E+02	24 %	5.15E+00	< 1 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

# Product Environmental Profile

**UNDER-DESK MULTI-OUTLETS to be connected -  
2P+E French and German standards sockets**



## SELECTION OF ENVIRONMENTAL IMPACTS

The environmental impact of the product, described in this document and different of the Reference Product, can be estimated by weighting the environmental impacts of the Reference Product by the corresponding factors.

Reference	Designation	coef to apply per phase of the life cycle					
		total Life Cycle	Raw materials and manufacture	Distribution	Installation	Use	End Of Life
073400	3x2P+E F/B empty	0.8	0.8	0.8	2.2	0.8	0.6
073401	4x2P+E F/B empty	0.8	0.8	0.8	0.9	0.9	0.8
<b>073402</b>	<b>6x2P+E F/B empty</b>	<b>1.0</b>	<b>1.0</b>	<b>1.0</b>	<b>1.0</b>	<b>1.0</b>	<b>1.0</b>
073403	3x2P+E F/B tamperproof empty	0.8	0.8	0.8	2.2	0.8	0.6
073404	4x2P+E F/B tamperproof empty	0.9	1.0	1.0	2.7	1.0	0.7
073405	2x2P+E F/B + 2x2P+E F/B tamperproof empty	1.3	1.1	1.1	2.6	1.9	0.9
073406	3x2P+E F/B + 3x2P+E F/B tamperproof empty	1.5	1.5	1.5	4.3	1.7	1.2
073419	2x2P+E F/B + 2x2P+E F/B tamperproof + 2RJ45 empty	1.5	1.2	1.2	2.5	2.1	1.1
073420	2xP+E German standard empty	0.8	0.8	0.8	2.3	0.9	0.6
073421	4xP+E German standard empty	1.1	1.0	1.0	2.5	1.5	0.8
073422	6xP+E German standard empty	1.3	1.4	1.4	4.2	1.2	1.0

Registration number: LGRP-01507-V01.01-EN	Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by «PSR-0003-ed1.1-2015 10 16»
Verifier accreditation N°: VH23	Information and reference documents: <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: 10-2022	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2016 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804: 2012 + A1 : 2013	

