

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME


CB TEST CERTIFICATE

Product	Multiple cord extension set
Name and address of the applicant	LEGRAND FRANCE 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE
Name and address of the manufacturer	LEGRAND FRANCE 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE
Name and address of the factory	NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD East Industrial Zone, Guanhaiwei Cixi City, 315314 ZHEJIANG PROVINCE - CHINA
Note: When more than one factory, please report on page 2	<input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	16 A, 250 V~, Max. 3680 W See Annex
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	/
Model / Type Ref.	050410, 050411
Additional information (if necessary may also be reported on page 2)	Supersedes CBTC FR_702203 dated 23/01/2018 (Update of the license for plug A14) <input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60884-1:2002+A1:2006 +A2:2013 IEC 60884-2-7:2011+A1:2013
As shown in the Test Report Ref. No. which forms part of this Certificate	BAN-17NO0050ACSC-1, BAN-17NO0050ACSC-2

This CB Test Certificate is issued by the National Certification Body



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 18/05/2018

Signature: **Jean-François BRUEL**
Certification Officer

ANNEX

REFERENCES - MAIN CHARACTERISTICS

Reference	Number of socket	With USB	With CBE	Colour of enclosure
050410	3	Yes	Yes	White
050411				Black

(CBE: circuit-breaker for equipment)


standard Sheet:	standard sheet V (CEE 7)
rated current (A)	16 A
rated load (W)	Max. 3680 W
rated voltage (V)	250 V~
household voltage (V)	230 V~
degree of protection	IP20
provision for earthing	with earthing contact
method of connecting the cable	non-rewirable
type of connections	soldered–other
colour	other
socket-outlets	
multiple socket-outlets	
number of socket-outlets	16 A :3
degree of protection against electric shock	normal protection
existence of shutters	with shutters
method of application - mounting	portable type
plugs:	
class of equipment	I

Components	Type / Reference	Manufacturer	Conformity
Plug	A14	Legrand	LCIE (NF)
Cable	HO3RT-H 3x1,5mm ²	Yuyao Nan Xiang	VDE
USB	Built-in	Legrand	LCIE (Test report No. BAN-17NO0280VTSC)
CBE	SS-006	Approach	*Test report No. 1711990020

*Test report issued by Zhejiang Fangyuan Test Group Co., Ltd



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



LABORATOIRE CENTRAL DES
INDUSTRIES ELECTRIQUES
S.A.S au capital de 15045000 €
RCS Nanterre 408 963 174
33 Avenue du Général Leclerc
F – 92266 FONTENAY AUX ROSES

Date: 18/05/2018

Signature: **Jean-François BRUEL**
Certification Officer