



Power **25 W**

Luminous flux* **2650 lm (90°)**

Colour of light **Neutral white**

Degree of protection (IP) **IP20**

Voltage **230 V**

Colour temperature **4000 K**

Beam angle **36, 60 °**



See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI033019NW
Power	25 W
Nominal current	120 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	LIFUD
Power factor	0.9
Useful luminous flux*	2650 lm (90°)
Luminous flux**	2650 lm (360°)
Lamp efficacy	106 lm/W
Luminous intensity	6100 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	36, 60 °
RA	80
Light source included	+
Producer of LED diodes	SANAN
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	170 x 160 x 74 mm
Weight	1.041 kg
For use	Inside
Assembly method	On 3-circuit system
Application	INT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux
Includes reflectors that allow you to change the beam angle (36°, 60°).