

90° elbow fitting with male metric thread according to EN 60423 for fixing the ends of flexible corrugated conduits to the cable entries on control panels, terminal boxes on electric motors, etc., in accordance with standard EN 60204 (Safety of Machinery). They are notable for their high tensile strength and tightness

Racores en ángulo de 90° con rosca macho métrica según EN 60423 para la fijación de tubos anillados flexibles a las entradas de cables en cuadros de maniobra, cajas de bornes en motores, etc., conforme a la norma EN 60204 (seguridad de las máquinas). Se distinguen por su gran resistencia a la tracción y alta estanqueidad

- Made of specially modified polyamide (PA6)
- Free of halogen, phosphorus and cadmium
- Self-extinguishing
- Shock-resistant
- Temperature range: -40°C to +105°C (150°C short term)
- IP66 protection. IP68/IP69 with ORJ and PLJ sealings
- “Easy-click”: quick assembly and removal of the conduit without tools
- Colours: dark grey and black

- Fabricados en poliamida especial modificada (PA6)
- Libres de halógenos, fósforo y cadmio
- Autoextinguibles
- Gran resistencia al impacto
- Gama de temperaturas: de -40°C a +105°C (150°C por breve tiempo)
- Protección IP66. IP68/IP69 con juntas ORJ y PLJ
- “Easy-click”: montaje y desmontaje instantáneo del tubo sin útiles
- Colores gris oscuro y negro

reference GREY GRIS	referencia BLACK NEGRO	ND		Ø int.	A	B	C	D	H	LR	Packing u Embalaje u
NEC-10M16G	NEC-10M16N	10	M16x1,5	10,0	35	42	21	21	11	11	50
NEC-12M16G	NEC-12M16N	12	M16x1,5	10,5	39	44	25	23	15	11	50
NEC-12M20G	NEC-12M20N	12	M20x1,5	12,3	39	45	25	26	15	11	50
NEC-17M20G	NEC-17M20N	17	M20x1,5	14,5	45	58	30	30	18	11	50
NEC-23M25G	NEC-23M25N	23	M25x1,5	18,5	53	66	36	37	23	12	30
NEC-29M32G	NEC-29M32N	29	M32x1,5	25,5	66	76	45	46	27	15	20
NEC-36M40G	NEC-36M40N	36	M40x1,5	32,0	79	89	54	55	33	19	10
NEC-48M50G	NEC-48M50N	48	M50x1,5	42,0	92	103	68	69	39	19	10

Dimensions in mm | Dimensiones en mm

