

Straight female connector for male thread *Racor hembra para rosca métrica*

FPR-M

Straight female thread connector to combine with other male metric thread elements such as straight MIR fittings (conduit coupler), rigid conduit connectors or cable glands. In accordance with standard EN 60204 (Safety of Machinery). They are notable for their high tensile strength and tightness

- Made of specially modified polyamide (PA6)
- Free of halogen, phosphorus and cadmium
- Self-extinguishing
- Shock-resistant
- Temperature range: -40°C to +105°C (150°C short term)
- IP66 protection. IP68/IP69 with ORJ and PLJ sealings
- “Easy-click”: quick assembly and removal of the conduit without tools
- Colours: dark grey and black

Racores rectos con rosca hembra para combinar con otros elementos con rosca macho métrica como por ejemplo racores rectos MIR (manguito de tubo), conectores para tubo rígido o prensaestopas. De acuerdo con el estándar EN 60204 (seguridad en maquinaria). Se distinguen por su gran resistencia a la tracción y alta estanqueidad

- Fabricados en poliamida especial modificada (PA6)
- Libres de halógenos, fósforo y cadmio
- Autoextinguibles
- Gran resistencia al impacto
- Gama de temperaturas: de -40°C a +105°C (150°C por breve tiempo)
- Protección IP66. IP68/IP69 con juntas ORJ y PLJ
- “Easy-click”: montaje y desmontaje instantáneo del tubo sin útiles
- Colores gris oscuro y negro

reference GREY GRIS	referencia BLACK NEGRO	ND		Ø int.	A	C	D		LR	Packing u Embalaje u
FPR-10M16G FPR-10M16N		10	M16x1.5	10.5	42	21	23	18	13	50
FPR-12M20G FPR-12M20N		12	M20x1.5	14.0	37	25	27	20	10	50
FPR-17M25G FPR-17M25N		17	M25x1.5	19.5	47	31	33	27	15	50
FPR-23M32G FPR-23M32N		23	M32x1.5	28.0	55	37	39	34	15	30
FPR-29M40G FPR-29M40N		29	M40x1.5	27.0	57	46	49	42	17	10
FPR-36M50G FPR-36M50N		36	M50x1.5	38.0	64	54	62	50	21	10
FPR-48M63G FPR-48M63N		48	M63x1.5	49.0	67	69	72	66	19	5

Dimensions in mm | Dimensiones en mm

