## Sound-insulation box 68



## One-gang box sound insulation 68 halogen-free

· for sound insulation walls

- · also for directly opposing installation
- minimum wall thickness 100 mm
- $\cdot\;$  can be combined with each other and with the one-gang junction box

| Order number:                       | 9069-75       |
|-------------------------------------|---------------|
| EAN:                                | 4013456547933 |
| Depth                               | 49 mm         |
| Cut hole Ø                          | 68 mm         |
| Tube entries up to M25              | 2             |
| Cable entries of up to Ø 11.5 mm    | 4             |
| Support connectors for each package | 5             |
| For panel thicknesses up to         | 40 mm         |
| for sound insulation walls up to    | 69 dB         |
| Halogen-free                        | Yes           |
| Packaging inner/dispatch            | 10/100        |

Thanks to their solid box body in combination with the sound-absorbing surface on the base of the box, sound insulation 68 one-gang and one-gang junction boxes guarantee the wall's sound insulation. This function is completely maintained even with directly opposing installation. The easy opening process and the 68 mm installation opening ensure fast mounting and also easy retrofitting in existing electrical installations.

- · Maintains the wall's sound insulation protection
- · Also for retrofitting
- · For Ø 68 mm installation openings
- · For directly opposing installation
- · Easy entry for cables up to Ø 11.5 mm and conduits up to Ø M25



