

## Cable glands Progress® stainless and acid-resistant steel A4 for high temper

**Long entry thread Pg**

- Two-piece sealing insert
- not overall length insulated

|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| <b>Order number:</b>               | <b>1100.48.98</b>                                                                 |
| EAN:                               | 7611614132655                                                                     |
| Material                           | Stainless steel and acid resistant steel A4<br>CrNiMo (DIN EN 1.4435 / AISI 316L) |
| Identification                     | 2 grooves                                                                         |
| Seal                               | FPM                                                                               |
| O-ring                             | FPM                                                                               |
| Operation temperature              | -40°C / +200°C                                                                    |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                                                      |
| Entry thread                       | Pg 48                                                                             |
| Clamping range with insert min.    | 37.0 mm                                                                           |
| Clamping range with insert max.    | 43.0 mm                                                                           |
| Clamping range without insert min. | 43.0 mm                                                                           |
| Clamping range without insert max. | 49.0 mm                                                                           |
| Wrench size                        | 65 mm                                                                             |
| Dimension H                        | 37 mm                                                                             |
| Thread length L                    | 15 mm                                                                             |
| Dispatch                           | 10                                                                                |