



---

|                 |                      |
|-----------------|----------------------|
| Power           | <b>5 W</b>           |
| Luminous flux** | <b>470 lm (360°)</b> |
| Colour of light | <b>WW</b>            |
| Socket          | <b>E14</b>           |

---

|                    |               |
|--------------------|---------------|
| Voltage            | <b>230 V</b>  |
| Colour temperature | <b>3000 K</b> |
| Beam angle         | <b>160 °</b>  |



 Declaration of Conformity

**Technical data:**

|                              |                                    |
|------------------------------|------------------------------------|
| Code                         | WOJ+14381_5W                       |
| Power                        | 5 W                                |
| Nominal current              | 25 mA                              |
| Voltage                      | 230 V                              |
| Energy efficiency class      | F                                  |
| Energy consumption           | 5 kWh/1000h                        |
| Frequency                    | 50HZ Hz                            |
| Power factor                 | 0.8                                |
| Useful luminous flux*        | 470 lm (360°)                      |
| Luminous flux**              | 470 lm (360°)                      |
| Lamp efficacy                | 94 lm/W                            |
| Colour temperature           | 3000 K                             |
| Colour of light              | WW                                 |
| Beam angle                   | 160 °                              |
| RA                           | 80                                 |
| Uniformity of color SDCM max | 5                                  |
| Dimmable                     | Yes                                |
| Working temperature range    | -20/+40 °                          |
| Lifespan                     | 17000 h                            |
| Socket                       | E14                                |
| Dimension (AxBxC)            | 36x109 mm                          |
| For use                      | Inside                             |
| Application                  | INT                                |
| Made in                      | PRC                                |
| Other                        | WOJ+06586; Berker 2867 10, 2973; , |

