



CE

Power **6 W**

Voltage **230 V**


Colour temperature **6000 K**

Light colour **CW**

Beam angle **38 °**


Protection class **IP20**



 Declaration of Conformity

Technical data:

| | |
|------------------------------|---------------|
| Product code | SLI021030CW |
| Power | 6 W |
| Nominal current | 50 mA |
| Voltage | 230 V |
| Energy consumption | 6 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.5 |
| Luminous flux** | 440 lm (360°) |
| Light efficiency | 73 lm/W |
| Colour temperature | 6000 K |
| Light colour | CW |
| Beam angle | 38 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | SREBRNY |
| Dimension (axbxc) | 86xH65 mm |
| Mounting hole | fi 75 mm |
| Weight | 0.2 kg |
| For use | Inside |
| Assembly method | Recessed |
| Application | INT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux