



Power	20 W	Voltage	230 V
Luminous flux*	1600 lm (90°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	90 °
Protection class	IP20		



 Declaration of Conformity



 Photometric file



 3D model

Technical data:

Product code	SLI022008NW
Power	20 W
Nominal current	90 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	1600 lm (90°)
Luminous flux**	1600 lm (360°)
Light efficiency	80 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Protection class	IP20
Colour	White
Dimension (axbxc)	190x90 mm
Mounting hole	170 mm
Weight	0.5 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



*Applies to the LED source used, **Luminaire luminous flux
A version with CNBOP-PIB* certificate is also available (valid only in Poland).