SLI035002CW_WHITE



CE

Power	9 W	Voltage	24 V
Colour temperature	6000 K	Light colour	CW
Beam angle	120 °	IK	06
Protection class	IP20		

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

SLI035002CW_WHITE

Technical data:

Product code	SLI035002CW_WHITE
Power	9 W
Nominal current	375 mA
Voltage	24 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Luminous flux**	520 lm (360°)
Light efficiency	57 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	Yes
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	150x150x26 mm
Weight	0.275 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu