



Power	6-20 W	Voltage	230 V
Colour temperature	3000 K	Light colour	WW
Beam angle	40 °	UGR	<19
IK	06	Protection class	IP44



See more on dedicated page 





 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI043019WW_PW
Power	6-20 W
Nominal current	90 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	2200 lm (360°)
Luminous flux**	500-1700 lm (360°)
Light efficiency	110 lm/W
Luminous intensity	3000 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
IK	06
Protection class	IP44
Colour	White
Dimension (axbxc)	139x85 mm
Mounting hole	115 mm
Weight	0.58 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux