



|                    |                |                  |                      |
|--------------------|----------------|------------------|----------------------|
| Power              | <b>14-27 W</b> | Voltage          | <b>230 V</b>         |
| Colour temperature | <b>4000 K</b>  | Light colour     | <b>Neutral white</b> |
| Beam angle         | <b>40 °</b>    | UGR              | <b>&lt;19</b>        |
| IK                 | <b>06</b>      | Protection class | <b>IP44</b>          |



See more on dedicated page 



 Declaration of Conformity



 Photometric file

## Technical data:

|                              |                                      |
|------------------------------|--------------------------------------|
| Product code                 | SLI043020NW_PW                       |
| Power                        | 14-27 W                              |
| Nominal current              | 125 mA                               |
| Voltage                      | 230 V                                |
| Energy consumption           | 27 kWh/1000h                         |
| Frequency                    | 50HZ Hz                              |
| Protection class             | II                                   |
| Power supply included        | Yes                                  |
| Power factor                 | 0.9                                  |
| Useful luminous flux*        | 3250 lm (360°)                       |
| Luminous flux**              | 1300-2600 lm (360°)                  |
| Light efficiency             | 120 lm/W                             |
| Luminous intensity           | 4000 cd                              |
| Colour temperature           | 4000 K                               |
| Light colour                 | Neutral white                        |
| Beam angle                   | 40 °                                 |
| UGR                          | <19                                  |
| RA                           | >90                                  |
| Light source included        | Yes                                  |
| Uniformity of color SDCM max | 5                                    |
| Dimmable                     | No                                   |
| Working temperature range    | -20/+40 °                            |
| Lifespan                     | 50000 h                              |
| Housing material             | Aluminum                             |
| IK                           | 06                                   |
| Protection class             | IP44                                 |
| Colour                       | White                                |
| Dimension (axbxc)            | 169x95 mm                            |
| Mounting hole                | 140 mm                               |
| Weight                       | 0.8 kg                               |
| For use                      | Inside                               |
| Assembly method              | Recessed                             |
| Application                  | Inside                               |
| Made in                      | PRC                                  |
| Other                        | DIP SWITCH - regulowana moc oprawy , |



\*Applies to the LED source used. \*\*Luminaire luminous flux