



## CE

Power	10 W	Voltage	230 V
Colour temperature	3000 K	Light colour	WW
Beam angle	40 °	Protection class	IP20

CEL37NST1083040W

## LED PRO LUMINAIRE



## Technical data:

Product code	W0JP06294
Product code	10 W
Nominal current	43 mA
Voltaae	43 MA 230 V
	230 V 10 kWh/1000h
Energy consumption	50HZ Hz
Frequency Protection class	
Power supply included	li Yes
11.5	TRIDONIC
Manufacturer of power supply Power factor	
Useful luminous flux*	0.93
USEIUI IUITIITUUS TIUX**	1450 lm (360°)
Edititiodad Hox	1050 lm (360°)
Light efficiency	145 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	40 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Working temperature range	-20/+40°
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	169x139 mm
Weight	0.93 kg
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PL



\*Applies to the LED source used. \*\*Luminaire luminous flux