# SLI033002NW_24ST



CE

| | | | |
|---|---|---|---|
| Power | 26 W | Voltage | 230 V |
| Colour temperature | 4000 K | Light colour | Neutral white |
| Beam angle | 24 ° | Protection class | IP20 |




Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

# SLI033002NW_24ST

## Technical data:

| | |
|---|---|
| Product code | SLI033002NW_24ST |
| Power | 26 W |
| Nominal current | 125 mA |
| Voltage | 230 V |
| Energy consumption | 26 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Luminous flux** | 2000 lm (360°) |
| Light efficiency | 76 lm/W |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 24 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, GLASS |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 120x210x165 mm |
| Weight | 0.944 kg |
| For use | Inside |
| Assembly method | On 3-circuit system |
| Application | INT |
| Made in | PRC |




*Applies to the LED source used. **Luminaire luminous flux



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu