



CE

Power **36 W**
Luminous flux* **6300 lm (360°)**
Light colour **Neutral white**
UGR **22**



Voltage **230 V**
Colour temperature **4000 K**
Beam angle **120 °**
IK **08**



 Declaration of Conformity

Technical data:

Product code	SLI047006NW_PW
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.95
Useful luminous flux*	6300 lm (360°)
Luminous flux**	5200 lm (360°)
Light efficiency	175 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
UGR	22
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-30/+40 °
Lifespan	50000 h
Housing material	plastic
IK	08
Protection class	IP66
Colour	Gray/White
Dimension (axbxc)	1700x65x67 mm
Weight	1.48 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	L80B10 50000h MTBF 80000h ,



*Applies to the LED source used. **Luminaire luminous flux