LED PRO LUMINAIRE

# WOJP07158



CE

| | | | |
|---|---|---|---|
| Power | 27 W | Voltage | 230 V |
| Colour temperature | 4000 K | Light colour | Neutral white |
| Beam angle | 24 ° | Protection class | IP20 |

MDR47PRO2794024W



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

LED PRO LUMINAIRE

# WOJP07158

## Technical data:

| | |
|---|---|
| Product code | WOJP07158 |
| Power | 27 W |
| Nominal current | 129.1 mA |
| Voltage | 230 V |
| Energy consumption | 27 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Manufacturer of power supply | TCI |
| Power factor | 0.93 |
| Useful luminous flux* | 3375 lm (360°) |
| Luminous flux** | 2700 lm (360°) |
| Light efficiency | 125 lm/W |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 24 ° |
| RA | 90 |
| Light source included | + |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 3 |
| Dimmable | OPC |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 90x205x165 mm |
| Weight | 1.05 kg |
| For use | Inside |
| Assembly method | On 3-circuit system |
| Application | Inside |
| Made in | PL |
| Other | L90B10 - 73000h , |




*Applies to the LED source used. **Luminaire luminous flux



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu