



CE

Power **27 W**

Voltage **230 V**

Colour temperature **4000 K**

Light colour **Neutral white**

Beam angle **38 °**

Protection class **IP20**



 Photometric file



 3D model

CEL42PR02794038W\_DIM

**Technical data:**

Product code	WOJP05196
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	BOKE
Power factor	0.93
Useful luminous flux*	3375 lm (360°)
Luminous flux**	2700 lm (360°)
Light efficiency	125 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	38 °
RA	90
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	180x130 mm
Mounting hole	Ø145 mm
Weight	1.11 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



\*Applies to the LED source used. \*\*Luminaire luminous flux