



## CE

Power	19 W	Voltage	230 V
Colour temperature	4000 K	Light colour	Neutral white
Beam angle	15 °	Protection class	IP20


MDR49PR01984015W

## LED PRO LUMINAIRE



## Technical data:

Product code	W0JP07194
Power	19 W
Nominal current	90.9 mA
Voltage	230 V
Energy consumption	19 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Manufacturer of power supply	TCI
Power factor	0.93
Useful luminous flux*	2850 lm (360°)
Luminous flux**	2090 lm (360°)
Light efficiency	150 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	15 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	84x190x160 mm
Weight	1.315 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL



Date of technical data: The date the document was created: 2024-03-05

\*Applies to the LED source used. \*\*Luminaire luminous flux