LED PRO LUMINAIRE

WOJP04252



CE

Power	19 W	Voltage	230 V
Colour temperature	3000 K	Light colour	WW
Beam angle	12 °	Protection class	IP20


Photometric file

MDD10PRO1983012B_DALI

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

Technical data:

Product code	WOJP04252
Power	19 W
Nominal current	90.9 mA
Voltage	230 V
Energy consumption	19 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	2660 lm (360°)
Luminous flux**	1710 lm (360°)
Light efficiency	140 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	12 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	Black
Dimension (axbxc)	82x115x100 mm
Mounting hole	92x92 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



*Applies to the LED source used. **Luminaire luminous flux

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu