



|                    |               |                  |              |
|--------------------|---------------|------------------|--------------|
| Power              | <b>17 W</b>   | Voltage          | <b>230 V</b> |
| Colour temperature | <b>3000 K</b> | Light colour     | <b>WW</b>    |
| Beam angle         | <b>90 °</b>   | Protection class | <b>IP20</b>  |



See more on dedicated page 

ALD11PRO178300PW

#### Technical data:

|                              |                   |
|------------------------------|-------------------|
| Product code                 | WOJP06908         |
| Power                        | 17 W              |
| Nominal current              | 81 mA             |
| Voltage                      | 230 V             |
| Energy consumption           | 24 kWh/1000h      |
| Frequency                    | 50HZ Hz           |
| Protection class             | I                 |
| Power supply included        | Yes               |
| Manufacturer of power supply | TRIDONIC          |
| Power factor                 | 0.93              |
| Useful luminous flux*        | 2465 lm (360°)    |
| Luminous flux**              | 1360 lm (360°)    |
| Light efficiency             | 145 lm/W          |
| Colour temperature           | 3000 K            |
| Light colour                 | WW                |
| Beam angle                   | 90 °              |
| RA                           | 80                |
| Light source included        | +                 |
| Producer of LED diodes       | SAMSUNG           |
| Uniformity of color SDCM max | 3                 |
| Dimmable                     | No                |
| Working temperature range    | -20/+40 °         |
| Lifespan                     | 50000 h           |
| Housing material             | Aluminum          |
| Protection class             | IP20              |
| Colour                       | White             |
| Dimension (axbxc)            | 560X44X74 mm      |
| Mounting hole                | 563X45 mm         |
| Weight                       | 0.8 kg            |
| For use                      | Inside            |
| Assembly method              | Recessed          |
| Application                  | Inside            |
| Made in                      | PL                |
| Other                        | L90B10 - 74000h , |



\*Applies to the LED source used. \*\*Luminaire luminous flux