



---

|                    |               |                  |                      |
|--------------------|---------------|------------------|----------------------|
| Power              | <b>27 W</b>   | Voltage          | <b>230 V</b>         |
| Colour temperature | <b>4000 K</b> | Light colour     | <b>Neutral white</b> |
| Beam angle         | <b>36 °</b>   | Protection class | <b>IP20</b>          |

---



 Photometric file

MDR47PRO2784036LW\_DIM

#### Technical data:

|                              |                     |
|------------------------------|---------------------|
| Product code                 | WOJP04699           |
| Power                        | 27 W                |
| Nominal current              | 129.1 mA            |
| Voltage                      | 230 V               |
| Energy consumption           | 27 kWh/1000h        |
| Frequency                    | 50HZ Hz             |
| Protection class             | I                   |
| Power supply included        | +                   |
| Manufacturer of power supply | BOKE                |
| Power factor                 | 0.93                |
| Useful luminous flux*        | 3780 lm (360°)      |
| Luminous flux**              | 3510 lm (360°)      |
| Light efficiency             | 140 lm/W            |
| Colour temperature           | 4000 K              |
| Light colour                 | Neutral white       |
| Beam angle                   | 36 °                |
| RA                           | 80                  |
| Light source included        | +                   |
| Producer of LED diodes       | CREE                |
| Uniformity of color SDCM max | 3                   |
| Dimmable                     | 1-10V               |
| Working temperature range    | -20/+40 °           |
| Lifespan                     | 50000 h             |
| Housing material             | Aluminum            |
| Protection class             | IP20                |
| Colour                       | White               |
| Dimension (axbxc)            | 90x200x185 mm       |
| Weight                       | 1.05 kg             |
| For use                      | Inside              |
| Assembly method              | On 3-circuit system |
| Application                  | Inside              |
| Made in                      | PL                  |
| Other                        | L90B10 - 73000h ,   |



\*Applies to the LED source used. \*\*Luminaire luminous flux