



Power **27 W**

Colour temperature **4000 K**

Beam angle **36 °**

Voltage **230 V**

Light colour **Neutral white**

Protection class **IP20**



 Photometric file




 3D model

MDR47PRO2784036LB_DIM

Technical data:

Product code	WOJP04703
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	BOKE
Power factor	0.93
Useful luminous flux*	3780 lm (360°)
Luminous flux**	3510 lm (360°)
Light efficiency	140 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	36 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	Black
Dimension (axbxc)	90x200x185 mm
Weight	1.05 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL
Other	L90B10 - 73000h ,



*Applies to the LED source used. **Luminaire luminous flux