LED PRO LUMINAIRE

WOJP04701



CE

Power	27 W	Voltage	230 V
Colour temperature	3000 K	Light colour	WW
Beam angle	36 °	Protection class	IP20

Photometric file

3D model

MDR47PRO2783036LB_DIM

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

Date of technical data:
The date the document was created: 2024-03-05

LED PRO LUMINAIRE

WOJP04701

Technical data:

Product code	WOJP04701
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	BOKE
Power factor	0.93
Useful luminous flux*	3510 lm (360°)
Luminous flux**	3510 lm (360°)
Light efficiency	130 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	36 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	Black
Dimension (axbxc)	90x200x185 mm
Weight	1.05 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL
Other	L90B10 - 73000h ,

*Applies to the LED source used. **Luminaire luminous flux

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu