

Power **46 W**

Voltage **230 V**


Colour temperature **3000 K**

Light colour **WW**


Beam angle **90 °**

Protection class **IP20**



See more on dedicated page 



 Declaration of Conformity



 Photometric file




 3D model

ALD9PR046830PRW

**Technical data:**

Product code	WOJP06317
Power	46 W
Nominal current	263 mA
Voltage	230 V
Energy consumption	46 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	6670 lm (360°)
Luminous flux**	5775 lm (360°)
Light efficiency	145 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	90 °
RA	80
Light source included	+
Producer of LED diodes	SAMSUNG
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	1680X44X74 mm
Weight	2.8 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL
Other	L90B10 - 74000h ,



\*Applies to the LED source used. \*\*Luminaire luminous flux