



Power **30 W**

Voltage **230 V**

Colour temperature **4000 K**

Light colour **Neutral white**

Beam angle **90 °**

Protection class **IP20**



See more on dedicated page 



 Photometric file



 3D model

ALD9PR030840PRW_DALI

Technical data:

Product code	WOJP06335
Power	30 W
Nominal current	167 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Manufacturer of power supply	OSRAM
Power factor	0.93
Useful luminous flux*	4350 lm (360°)
Luminous flux**	3675 lm (360°)
Light efficiency	145 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Light source included	+
Producer of LED diodes	SAMSUNG
Uniformity of color SDCM max	3
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	1120X44X74 mm
Weight	2.2 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL
Other	L90B10 - 74000h ,



*Applies to the LED source used. **Luminaire luminous flux