



|                |                        |                    |               |
|----------------|------------------------|--------------------|---------------|
| Power          | <b>200 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux* | <b>36000 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Light colour   | <b>Neutral white</b>   | Beam angle         | <b>90 °</b>   |
| IK             | <b>08</b>              | Protection class   | <b>IP65</b>   |



See more on dedicated page 




 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                     |
|------------------------------|---------------------|
| Product code                 | SLI044016NW_PW_DALI |
| Power                        | 200 W               |
| Nominal current              | 910 mA              |
| Voltage                      | 230 V               |
| Energy consumption           | 200 kWh/1000h       |
| Frequency                    | 50HZ Hz             |
| Protection class             | I                   |
| Power supply included        | Yes                 |
| Power factor                 | 0.9                 |
| Useful luminous flux*        | 36000 lm (360°)     |
| Luminous flux**              | 34000 lm (360°)     |
| Light efficiency             | 180 lm/W            |
| Luminous intensity           | 16000 cd            |
| Colour temperature           | 4000 K              |
| Light colour                 | Neutral white       |
| Beam angle                   | 90 °                |
| RA                           | >80                 |
| Light source included        | Yes                 |
| Uniformity of color SDCM max | 5                   |
| Dimmable                     | DALI                |
| Working temperature range    | -20 +40 °           |
| Lifespan                     | 50000 h             |
| Housing material             | Aluminum            |
| IK                           | 08                  |
| Protection class             | IP65                |
| Colour                       | Black               |
| Dimension (axbxc)            | 347x160 mm          |
| Weight                       | 3 kg                |
| For use                      | Inside/Outside      |
| Assembly method              | Suspended           |
| Made in                      | PRC                 |



\*Applies to the LED source used. \*\*Luminaire luminous flux