LED PRO LUMINAIRE

# WOJP05826



CE

| | | | |
|---|---|---|---|
| Power | 46 W | Voltage | 230 V |
| Colour temperature | 3000 K | Light colour | WW |
| Beam angle | 110 ° | Protection class | IP20 |

Photometric file


ALD2PRO468300PW_CASAMBI



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

## Technical data:

| | |
|---|---|
| Product code | WOJP05826 |
| Power | 46 W |
| Nominal current | 263 mA |
| Voltage | 230 V |
| Energy consumption | 46 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Manufacturer of power supply | OSRAM |
| Power factor | 0.93 |
| Useful luminous flux* | 6670 lm (360°) |
| Luminous flux** | 4400 lm (360°) |
| Light efficiency | 145 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 110 ° |
| RA | 80 |
| Light source included | + |
| Producer of LED diodes | SPECTRUM |
| Uniformity of color SDCM max | 3 |
| Dimmable | OPC |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 44x1710x35 mm |
| Mounting hole | 1700x33,5 mm |
| Weight | 3.24 kg |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PL |




*Applies to the LED source used. **Luminaire luminous flux



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu