



Power	<b>36 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5300 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>120 °</b>
IK	<b>08</b>	Protection class	<b>IP65</b>



 Declaration of Conformity

Technical data:

Product code	SLI028111CW_PW
Power	36 W
Nominal current	160 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.98
Useful luminous flux*	5300 lm (360°)
Luminous flux**	4300 lm (360°)
Light efficiency	147 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	PC/PC
IK	08
Protection class	IP65
Colour	Gray
Dimension (axbxc)	1200x64x60 mm
Weight	0.8 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,



\*Applies to the LED source used. \*\*Luminaire luminous flux