



Power **22 W**

Voltage **48 V**


Colour temperature **3000 K**

Light colour **WW**

Beam angle **100 °**

Protection class **IP20**



See more on dedicated page 



 Declaration of Conformity



 Photometric file



 3D model

Technical data:

| | |
|------------------------------|----------------|
| Product code | WLD+40039 |
| Power | 22 W |
| Nominal current | 435 mA |
| Voltage | 48 V |
| Energy consumption | 22 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 2300 lm (360°) |
| Luminous flux** | 1060 lm (360°) |
| Light efficiency | 105 lm/W |
| Luminous intensity | 360 cd |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 100 ° |
| RA | >90 |
| Light source included | Yes |
| Producer of LED diodes | osram |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 50000 h |
| Housing material | AL+PC |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 902x23x42 mm |
| Weight | 0.48 kg |
| For use | Inside |
| Assembly method | NA SZYŃĘ |
| Application | Inside |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux