



---

Power	<b>17 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000 K</b>	Light colour	<b>WW</b>
Beam angle	<b>35 °</b>	UGR	<b>&lt;19</b>
Protection class	<b>IP20</b>		

---



 Declaration of Conformity

Technical data:

Product code	WLD+40012_DALI
Power	17 W
Nominal current	350 mA
Voltage	48 V
Energy consumption	17 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	tuobo
Power factor	1
Useful luminous flux*	1700 lm (360°)
Luminous flux**	1150 lm (360°)
Light efficiency	100 lm/W
Luminous intensity	3100 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	35 °
UGR	<19
RA	>90
Light source included	Yes
Producer of LED diodes	osram
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Protection class	IP20
Colour	Black
Dimension (axbxc)	303x23x42 mm
For use	Inside
Assembly method	NA SZYNE
Application	Inside
Made in	PRC
Other	DALI ,



\*Applies to the LED source used. \*\*Luminaire luminous flux