



CE

---


Power	<b>5 W</b>
Colour temperature	<b>3000 K</b>
Beam angle	<b>165 °</b>
Protection class	<b>IP20</b>

Voltage	<b>48 V</b>
Light colour	<b>WW</b>
UGR	<b>&lt;19</b>

---

**Technical data:**

Product code	WLD+40000_CASAMBI
Power	5 W
Nominal current	100 mA
Voltage	48 V
Energy consumption	5 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	tuobo
Power factor	1
Useful luminous flux*	550 lm (360°)
Luminous flux**	435 lm (360°)
Light efficiency	110 lm/W
Luminous intensity	90 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	165 °
UGR	<19
RA	>90
Light source included	Yes
Producer of LED diodes	osram
Uniformity of color SDCM max	5
Dimmable	CASAMBI
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Protection class	IP20
Colour	White/Black
Dimension (axbxc)	100x148 mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC
Other	CASAMBI ,



\*Applies to the LED source used. \*\*Luminaire luminous flux