



product description: the bushings are designed to mechanically protect the conductors or cables coming from the steel pipe  
plug the bushing from outside on the end of pipe before installing cables

material: PE

halogen-free: yes

color: gray

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

meets the requirements: EN 61386-1 ed.2:09

storage: ČSN 64 0090



chemical resistance: YES: acetone, amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
NO: anilin, chlorinated hydrocarbons, tetrachlorocarbon

item number	di (mm)	dn outer Ø (mm)	weight 1pc (kg)	package (pcs)	for pipes
<b>4816E_KA</b>	12	16	0,001	100 / 3000	6016E..., 6216E...
<b>4820_KA</b>	16	20	0,001	100 / 1200	6020..., 6220...
<b>4825_KA</b>	21	25	0,003	100 / 800	6025..., 6225...
<b>4832_KA</b>	28	32	0,005	50 / 400	6032..., 6232...
<b>4840_KA</b>	35	40	0,007	50 / 200	6040..., 6240...
<b>4850_KA</b>	43	50	0,012	25 / 100	6050..., 6250...
<b>4863_KA</b>	57	63	0,022	10 / 70	6063..., 6263...