

type number	for width of cable tray (mm)	thickness of metal sheet (mm)	weight (kg/pc)
K 60X50_S	50	1,0	0,052
K 60X75_S	75	1,0	0,063
K 60X100_S	100	1,0	0,074
K 60X150_S	150	1,0	0,096
K 60X200_S	200	1,0	0,118
K 60X300_S	300	1,0	0,162
K 60X400_S	400	1,0	0,206
K 60X500_S	500	1,0	0,250
K 60X600_S	600	1,0	0,294
K 60X50_F	50	1,0	0,060
K 60X75_F	75	1,0	0,076
K 60X100_F	100	1,0	0,086
K 60X150_F	150	1,0	0,110
K 60X200_F	200	1,0	0,137
K 60X300_F	300	1,0	0,188
K 60X400_F	400	1,0	0,239
K 60X500_F	500	1,0	0,290
K 60X600_F	600	1,0	0,341



product description: The end-piece is used to cover the end of cable trays running through JUPITER cable trays.
 To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.
 A bolt with a GMT surface finish is used for a tray with an F surface finish.
 These items can also be ordered in a varnished version.

surface finish: S - Pre-Galvanized, zinc-layer 13 - 27 µm
 F - Hot Dip Galvanized according to EN ISO 1461, zinc-layer 45 µm (min. 35 µm)

sales amount: á 1 pc

meets the requirements: EN 61537:02

classification: ČSN 73 0895 P 90-R
 DIN 4102-12 E 90
 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire

Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

