

| type number         | for width of cable trays (mm) | for height of cable trays (mm) | B (mm) | C (mm) | thickness of metal sheet (mm) |
|---------------------|-------------------------------|--------------------------------|--------|--------|-------------------------------|
| <b>NT 50X62_S</b>   | 62                            | 50                             | 465    | 265    | 0,8                           |
| <b>NT 50X125_S</b>  | 125                           | 50                             | 528    | 328    | 0,8                           |
| <b>NT 50X250_S</b>  | 250                           | 50                             | 653    | 453    | 1,0                           |
| <b>NT 100X125_S</b> | 125                           | 100                            | 528    | 328    | 0,8                           |
| <b>NT 100X250_S</b> | 250                           | 100                            | 653    | 453    | 1,0                           |
| <b>NT 100X500_S</b> | 500                           | 100                            | 903    | 703    | 1,0                           |
| <b>NT 50X62_F</b>   | 62                            | 50                             | 465    | 265    | 0,8                           |
| <b>NT 50X125_F</b>  | 125                           | 50                             | 528    | 328    | 0,8                           |
| <b>NT 50X250_F</b>  | 250                           | 50                             | 653    | 453    | 1,0                           |
| <b>NT 100X125_F</b> | 125                           | 100                            | 528    | 328    | 0,8                           |
| <b>NT 100X250_F</b> | 250                           | 100                            | 653    | 453    | 1,0                           |
| <b>NT 100X500_F</b> | 500                           | 100                            | 903    | 703    | 1,0                           |



**product description:** The T-piece is used to branch off MARS cable trays of the same width.  
 It is possible to use reduction piece NRD to create branch of different width.  
 Use the bolt NSM 6X10 for connection. The bolt head should be inside the cable tray to protect the cables.  
 A bolt with a GMT surface finish is used for a tray with an F surface finish.  
 Accessories may be covered according to the description given in the Systems with Maintained Functionality during Fires catalogue.

**surface finish:** S - Pre-Galvanized, zinc-layer 15 - 27 µm  
 F - Hot Dip Galvanized, zinc-layer 50 - 100 µm  
 EO - epoxy paint for indoor environment - paint over the perimeter - 60 µm  
 EC - epoxy paint for indoor environment - total paint - 60 µm

**sales amount:** á 1 pc

**meets the requirements:** EN 61537:02

**classification:** ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90  
 Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

**storage:** EN 60721-3-1

