

Opis produktu

64765-82-500

64765-82-500 Comfort switch flex sensor



Ogólne informacje

Typ produktu	64765-82-500
Kod zamówieniowy	2CKA006800A2885
Numer EAN	4011395293065
Opis katalogowy	64765-82-500 Comfort switch flex sensor
Opis	<p>Movement detector push-button switch combination. For switching lighting systems that depend on brightness and movement. With select lens, prevents detection of smaller animal. Push switch function possible at all times. With notice LED when manual operation is necessary. Extension of the detection range by main unit/extension unit combination. Control element: 2 controllers for setting the brightness switching threshold and switch-off delay. Additional activation/deactivation option via push-button input on the flush-mounted insert. Adjustable operating mode: automatic mode, automatic (motion-controlled) switch-on and switch-off. Adjustable operating mode: semiautomatic, manual switch-on, automatic (timer and movement-controlled) switch-off. Adjustable operating mode: automatic mode, automatic switch-on, manual switch-off. With continuous light/continuous Off function. Adjusting elements on rear side. Surveillance density: 9 sectors with 28 switching segments. Switch off delay: 1 to 10 min., adjustable. Compatible with all ABB flexTronics inserts. For relay insert flex, 1gang, 64811 U-500 For relay insert flex, 2gang, 64821 U-500. For e-contact insert flex, 1gang, 64814 U-500. For LED touch dimmer insert flex, 1gang, 64851 U-500. For extension insert flex, 64891 U-500. Display elements: LED for status display. Control element: 2 controllers for setting the brightness switching threshold and switch-off delay. Brightness limit value: 5 Lux - daytime operation Height above the wall: 21 mm. The range specifications refer only to an ambient temperature of 21°C. Please order the respective flush-mounted insert separately.</p>

Informacje dodatkowe

Temperatura powietrza otoczenia	0...35 °C
Funkcja aplikacji	Electrical Load and Light Control
Marka	ABB
CN8	8538 90 99
Kolor	ivory white
Szablon raportowania CMRT	9AKK108468A3363
Kraj pochodzenia	Niemcy (DE)
Kod taryfy celnej	85389099
Arkusze danych, informacje techniczne	No document needed
Karta danych, informacje techniczne (część 2)	2CKA000073B5216
Deklaracja zgodności UE	No declaration needed
Stopień ochrony	IP20
Cykl pracy	Maximum 10 minute [unit of time]
Numer EAN	4011395293065

eClass	V11.0 : 27144008
ETIM 7	EC000138 - Sensor element for movement sensor
ETIM 8	EC000138 - Sensor element for movement sensor
Instrukcje i podręczniki	2CKA000073B5200 2CKA000073B5201 2CKA000073B5202 2CKA000073B5206 2CKA000073B5207 2CKA000073B5210
Opis	64765-82-500 Comfort switch flex sensor
Materiał	Thermoplastic
Minimalna ilość zamówienia	1 sztuka
Minimalny czas przełączania	Switch-On 60 second [unit of time]
Rodzaj pomiaru	Movement sensor
Typ montażu	Flush Mounted
Długość opakowania (poziom 1)	78 mm
EAN opakowania (poziom 1)	4011395293065
Waga opakowania brutto (poziom 1)	0.11 kg
Wysokość opakowania (poziom 1)	58 mm
Jednostkowe opakowanie	carton 1 sztuka
Szerokość opakowania (poziom 1)	92 mm
Głębokość / długość netto	32 mm
Wysokość netto	63 mm
Masa netto	38 g
Szerokość netto	63 mm
Grupa produktowa	flexTronics
Kolor RAL	RAL 1013 - Oyster White
Deklaracja REACH	2CKA309999E9999
Data RoHS	20201020
Dane RoHS	2CKA200000E7313
Status RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Jednostka sprzedaży	sztuka
Krótki opis	64765-82-500 Comfort switch flex sensor
Zasięg transmisji	Frontally 5 m Sideways 3 m
WEEE B2C / B2B	Business To Consumer
Kategoria WEEE	5. Small Equipment (No External Dimension More Than 50 cm)
ETIM 9	EC000138 - Sensor element for movement sensor
Design Range	solo Busch-Duro 2000 Busch-axcent Busch-balance SI Busch-Dynasty carat

future linear
 Pure Stainless Steel
 Reflex SI/SI Linear
 Busch-axcent pur
 future
 63x63
 Busch-Duro 2000 SI Linear
 Reflex SI
 Reflex SI Linear

Application Sub Function	Switching Dimming Motion Detection
REACH Information	False - does not contains substances > 0.1 mass percentage
REACH Date	20230825

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A3042	Relay insert 1 gang(s) 230 V	64811 U-500	1	sztuka
2CKA006800A3045	Relay insert 2 gang(s) 230 V	64821 U-500	1	sztuka
2CKA006800A3048	Standard Outputs 1 gang(s) 230 V	64814 U-500	1	sztuka
2CKA006500A0013	Dimmer insert Push button 1 gang(s) 230 V	64851 U-500	1	sztuka
2CKA006800A3051	Bus Coupling Units / Push Button Coupling Units 1 gang(s) 230 V	64891 U-500	1	sztuka

