

Opis produktu

64765-92-507

Electronic Controls Movement sensor white -
Basic55



Ogólne informacje

| | |
|------------------|---|
| Typ produktu | 64765-92-507 |
| Kod zamówieniowy | 2CKA006800A2903 |
| Numer EAN | 4011395293188 |
| Opis katalogowy | Electronic Controls Movement sensor white - Basic55 |

| | |
|------|---|
| Opis | <p>Movement detector push-button switch combination. For switching lighting systems that depend on brightness and movement. With select lens, prevents detection of smaller animal. Push switch function possible at all times. With notice LED when manual operation is necessary. Extension of the detection range by main unit/extension unit combination. Control element: 2 controllers for setting the brightness switching threshold and switch-off delay. Additional activation/deactivation option via push-button input on the flush-mounted insert. Adjustable operating mode: automatic mode, automatic (motion-controlled) switch-on and switch-off. Adjustable operating mode: semiautomatic, manual switch-on, automatic (timer and movement-controlled) switch-off. Adjustable operating mode: automatic mode, automatic switch-on, manual switch-off. With continuous light/continuous Off function. Adjusting elements on rear side. Surveillance density: 9 sectors with 28 switching segments. Switch off delay: 1 to 10 min., adjustable. Compatible with all ABB flexTronics inserts. For relay insert flex, 1gang, 64811 U-500 For relay insert flex, 2gang, 64821 U-500. For e-contact insert flex, 1gang, 64814 U-500. For LED touch dimmer insert flex, 1gang, 64851 U-500. For extension insert flex, 64891 U-500. Display elements: LED for status display. Control element: 2 controllers for setting the brightness switching threshold and switch-off delay. Brightness limit value: 5 Lux - daytime operation Height above the wall: 21 mm. The range specifications refer only to an ambient temperature of 21°C. Please order the respective flush-mounted insert separately.</p> |
|------|---|

Installation

| | |
|--------------------------|--|
| Instrukcje i podręczniki | 2CKA000073B5200 2CKA000073B5201 2CKA000073B5202 2CKA000073B5206 2CKA000073B5207 2CKA000073B5210 |
| Typ montażu | Flush Mounted |

Dane techniczne

| | |
|---|------------------------------------|
| Arkusze danych, informacja techniczna | No document needed |
| Karta danych, informacje techniczne (część 2) | 2CKA000073B5216 |
| Grupa produktowa | flexTronics |
| Minimalny czas przełączania | Switch-On 60 second [unit of time] |

Design

| | |
|--------------|-------------------------|
| Design Range | Basic55 |
| Materiał | Thermoplastic |
| Kolor RAL | RAL 1013 - Oyster White |
| Kolor | white |

Material Compliance

| | |
|---------------------------|--|
| Dane RoHS | 2CKA200000E7327 |
| Status RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Deklaracja REACH | 2CKA309999E9999 |
| REACH Information | False - does not contains substances > 0.1 mass percentage |
| Szablon raportowania CMRT | 9AKK108468A3363 |

Normy środowiskowe

| | |
|---------------------------------|-----------|
| Temperatura powietrza otoczenia | 0...35 °C |
| Stopień ochrony | IP20 |

Wymiary

| | |
|---------------------------|---------|
| Szerokość netto | 55 mm |
| Wysokość netto | 55 mm |
| Głębokość / długość netto | 30.5 mm |
| Masa netto | 33 g |

Certyfikaty i deklaracje (Numer dokumentu)

| | |
|-------------------------|-----------------------|
| Deklaracja zgodności UE | No declaration needed |
|-------------------------|-----------------------|

Klasyfikacje

| | |
|----------------|--|
| ETIM 9 | EC000138 - Sensor element for movement sensor |
| eClass | V11.0 : 27144008 |
| Kategoria WEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|--|-------------|----------|-----------------|
| 2CKA006800A3042 | Relay insert 1 gang(s) 230 V | 64811 U-500 | 1 | sztuka |
| 2CKA006800A3045 | Relay insert 2 gang(s) 230 V | 64821 U-500 | 1 | sztuka |
| 2CKA006800A3048 | Standard Outputs 1 gang(s) 230 V | 64814 U-500 | 1 | sztuka |
| 2CKA006500A0013 | Dimmer insert Push button 1 gang(s) 230 V | 64851 U-500 | 1 | sztuka |
| 2CKA006800A3051 | Bus Coupling Units / Push Button Coupling Units 1 gang(s) 230 V | 64891 U-500 | 1 | sztuka |

Kategorie

Produkty niskiego napięcia i systemy → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls

