

Opis produktu

64762-81-500

## Busch-Watchdog Cover plate Movement sensor anthracite - 63x63



### Ogólne informacje

Typ produktu	64762-81-500
Kod zamówieniowy	2CKA006800A2958
Numer EAN	4011395293522
Opis katalogowy	Busch-Watchdog Cover plate Movement sensor anthracite - 63x63

Opis

Movement detector sensor with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times. ./.

In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Adjusting elements on rear side. Extension of the detection range by means of master/slave combination. With continuous light/continuous Off function.

With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 14 sectors with 56 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U. For LED touch dimmer insert flex, 1gang, 64851 U. For extension insert flex, 64891 U. Mounting height: 22 mm.

### Installation

Instrukcje i podręczniki	2CKA000073B5100 2CKA001373B5203 2CKA001473B5204
Typ montażu	Flush Mounted

## Dane techniczne

Arkusze danych, informacje techniczne	2CKA001373B5203
Karta danych, informacje techniczne (część 2)	2CKA000073B5216
Grupa produktowa	flexTronics
Minimalny czas przełączania	Switch-On 10 second [unit of time]

## Design

Design Range	63x63 future linear Busch-axcent Busch-axcent pur Busch-Dynasty carat
Materiał	Thermoplastic
Kolor RAL	RAL 7021 - Black Grey
Kolor	anthracite

## Material Compliance

Dane RoHS	2CKA200000E7337
Status RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Deklaracja REACH	2CKA309999E9999
REACH Information	False - does not contains substances > 0.1 mass percentage
Szablon raportowania CMRT	9AKK108468A3363

## Normy środowiskowe

Temperatura powietrza otoczenia	Eksploatacja -5 ... +45 °C
Stopień ochrony	IP20

## Wymiary

Szerokość netto	63 mm
Wysokość netto	63 mm
Głębokość / długość netto	35 mm
Masa netto	34 g

## Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności UE	2CKA100000E4281
-------------------------	-----------------

## Klasyfikacje

ETIM 9	EC000138 - Sensor element for movement sensor
eClass	V11.0 : 27144008

Kategoria WEEE

5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B

Business To Consumer

---

**Accessories**

---

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A3042	Relay insert 1 gang(s) 230 V	64811 U-500	1	sztuka
2CKA006800A3048	Standard Outputs 1 gang(s) 230 V	64814 U-500	1	sztuka
2CKA006800A3045	Relay insert 2 gang(s) 230 V	64821 U-500	1	sztuka
2CKA006500A0013	Dimmer insert Push button 1 gang(s) 230 V	64851 U-500	1	sztuka
2CKA006800A3051	Bus Coupling Units / Push Button Coupling Units 1 gang(s) 230 V	64891 U-500	1	sztuka

---

**Kategorie**

---

Produkty niskiego napięcia i systemy → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Electronic Controls

